

## MATERIAALIT

Runko kromattua, harmaata tai mustaa teräsputkea. Istuin pehmustettua ja verhoiltua vaneria.



# MATCH

■ NOWY STYL GROUP® ■

## VERHOILUVAIHTOEHDOT

ryhmä 1: Bondai, Kaiman, Lucia, Sempre

ryhmä 2: Conctract, Era, Microfibra, Nexus, Valencia, Xtreme

ryhmä 3: King L Elast, Oxygen, Silvertex, Flex, Runner

ryhmä 4: Blazer, Fame, Synergy

ryhmä 5: Fine Leather Le, Fine Leather SD

ryhmä 6: Designo Leather

## JALKAVAIHTOEHDOT

Nelipistejalka. Lenkkijalka.

## PINOTTAVUUS

Max. 3 tuolia.


## LISÄVAIHTOEHDOT

Huopatallat. RivikytKentä. Verhoillun istuimen pinoamissuoja.


## TAKUU

Tuotteilla on 5 vuoden takuu.


## 1. Dimensions/Weight



**MATCH-30-A**  
weight: 9 kg



**MATCH-40**  
weight: 9 kg



**MATCH-40-A**  
weight: 9 kg

## 2. Materials/Versions

### 2.1. Frame

Tube frame in quality steel ( $\varnothing 25 \times 2 \text{ mm}$ ).  
Surface available in chrome, powder coated silver metallic or black.  
Stacking: up to 3 pieces.

### 2.2. Armrest pad

Artificial leather (black).

### 2.3. Glides

Felt glides for hard floors (option).

### 2.4. Seat and back plate

Seat and back plates made of plywood, 10 mm.  
Ergonomically shaped seat and back parts.

### 2.5. Cushion

Produced from CFC-free PU cut foam.  
Seat density:  $40 \text{ kg/m}^3 \pm 3$ .  
Back density:  $35 \text{ kg/m}^3 \pm 3$ .  
Seat cushion thickness: 40 mm.  
Back cushion thickness: 20 mm.

### 2.6. Screws, nuts, washers

Chromium plated (galvanic coating).

### 2.7. Metal parts

Heavy metal free epoxy resin powder coating  
(coating thickness at least.  $70 \mu\text{m}$ ).

### 2.8. Welding connections

Inert gas welding.

## 3. Packaging

2 pieces per box (assembled).

## 4. Technical regulations, certificates and quality marks

GS Safety Certificate.  
Quality Office certified.

